

产品类别 Product Category	牌号 Grade	测试标准、测试项目 Test criteria, test items							特性及用途 Property and Application
		熔指 MFI g/10min	密度 Density g/cm ³	拉伸强度 Tensile Strength MPa	弯曲强度 Flexural Strength Mpa	弯曲模量 Flexural modulus Mpa	悬臂梁缺口冲击强度 Notched Izod impact strength J/m	阻燃性 Flame retardance	
		ASTM D1238	ASTM D792	ASTM D638	ASTM D790		ASTM D256	UL 94	
玻纤增强 ABS GF Reinforced ABS	RF1020G10	14, 220°C, 10kg	1.11	60	90	4000	85	1.5mm HB	高强度、低应力, 扇叶 High strength, low stress, fan blade
	RF1020G20	8, 220°C, 10kg	1.18	90	130	6500	75	1.5mm HB	高强度、尺寸稳定, 扇叶 High strength, stable size, fan blade
	RF1020G30	6, 220°C, 10kg	1.26	120	140	7500	70	1.5mm HB	高强度、尺寸稳定, 扇叶 High strength, stable size, fan blade
阻燃增强 ABS Reinforced flame-retarded ABS	FR1020G10	26, 220°C, 10kg	1.26	60	90	4000	80	1.5mm V0 2.5mm 5VA	高强度、耐高温, 扇叶 High strength, high temperature resistance, fan blade
	FR1020G20	20, 220°C, 10kg	1.34	85	130	6500	70	1.5mm V0 2.5mm 5VA	高强度、高阻燃, 扇叶 High strength, high flame retardancy, fan blade
	FR1020G30	15, 220°C, 10kg	1.42	115	130	7500	65	1.5mm V0 2.5mm 5VA	高强度、高阻燃, 扇叶 High strength, high flame retardancy, fan blade