

产品类别 Product Category	牌号 Grade	测试标准、测试项目 Test criteria, test items							特性及用途 Property and Application
		熔指 MFI g/10min	密度 Density g/cm ³	拉伸强度 Tensile Strengt h MPa	弯曲强 度 Flexur al Strength Mpa	弯曲模量 Flexural modulus Mpa	悬臂梁缺口 冲击强度 Notched Izod impact strength J/m	紫外耐候性 Uv weather resistance	
		ASTM D1238	ASTM D792	ASTM D638	ASTM D790		ASTM D256	ASTM D 4329A	
耐候ABS Weather resistant ABS	HRABS- RS	25, 220°C, 10kg	1.05	45	70	2200	200	ΔE≤1.0	高强度、高耐候, 白电外壳 High strength, high weather resistance, white home application shell
高光ABS High gloss ABS	HRABS- HG	23, 220°C, 10kg	1.06	50	75	2100	180	ΔE≤3.0	高强度、高光泽, 白电外壳 High strength and high luster white home application shell
高流动ABS High flow ABS	HRABS- CR (+)	35, 220°C, 10kg	1.06	50	75	2200	170	ΔE≤3.0	高流动、高光泽, 白电外壳 High flow, high luster, white home application shell
高光ABS合 金 High gloss ABS alloy	HG-1039	25, 220°C, 10kg	1.08	45	70	2000	150	ΔE≤3.0	高光泽, 高硬度, 白电外壳 High luster, high hardness, white home application shell